



PRODUCT BRIEF > OPTICAL

Optical DSP

Dove 800D



800Gbps PAM-4 DSP with Integrated VCSEL Driver

Dove 800D (CFD73801) is a versatile full-duplex device with industry-leading power dissipation that is ideal for next-generation, low-power, high-performance 2x400G, or 1x800G OSFP and QSFP-DD800 optical transceivers and AOCs.

The device includes the industry's first monolithically integrated CMOS VCSEL drivers and fourth generation DSP technology which together creates an optimized, high-performance, small footprint solution that meets increasingly stringent energy efficiency requirements. The Dove 800D is tailored for multimode optical fiber (MMF) applications.


Dedicated PLLs for each transmit and receive data lane enable a wide range of breakout applications. High-performance optical and electrical host side DSP technology, together with specialized performance enhancing features, compensate for optical and electrical impairments while maintaining low-power dissipation.

Applications

- AI
- Hyperscale data centers
- Cloud networks
- 800GbE or 2x400GbE optical transceivers and AOCs
- Breakout applications

Key Parameters

Host Side	8x106G PAM4
Line Side	8x106G PAM4
Operating Temp	0° to 85°C



Key Features

- 100G PAM4 on both the electrical host and optical line side
- Fourth generation DSPs on optical side and electrical side deliver industry leading sensitivity and BER performance, providing margin for component variation and high-volume manufacturing
- Line side Rx performance-enhancing features tailored to address optical impairments in stressful MMF environment
- Integrated 100G VCSEL drivers with programmable laser currents to optimize module layout and reduce BOM costs
- High-performance transmitters come with multi-tap FIR filters, allowing precision optimization at both the module electrical connector and optical interface
- Host side interface supports extended PCB reach without the need for customized per-channel settings
- Independent phase locked loops per channel support flexible breakout configurations including 8x100G, 2x400G, 4x200G and 8x100G
- Full suite of test features and loopbacks simplifies lab bring up and production testing to reduce time-to-market
- Low-power dissipation enables higher rack utilization and lower thermal cooling requirements

Supported Standards and Interfaces

- 800G-SR8
- 400G-SR4
- 400GAUI-4, 800GAUI-8 C2M
- CEI-112G-VSR-PAM4
- CEI-112G-MR-PAM4
- OSFP and QSFP-DD800
- CMIS 4.x and 5.x

About Credo

Credo's mission is to advance high-speed connectivity solutions that deliver optimized performance, reliability, energy efficiency, and security for the next generation of AI driven applications, cloud computing, and hyperscale networks.

Optimized for both optical and electrical applications, our solutions support port speeds up to 1.6Tb. At the core of our technology is our proprietary Serializer/Deserializer (SerDes) IP. Our diverse solutions portfolio includes system-level products such as Active Electrical Cables (AECs), a range of Integrated Circuits, including Retimers, Optical DSPs, SerDes chipsets, and SerDes IP Licensing.

For more information please visit www.credosemi.com
or email sales@credosemi.com

© 2025 Credo Semiconductor, Inc. All Rights Reserved. Credo Semiconductor Inc. and the Credo logo are trademarks of Credo Semiconductor Inc. All other marks are the property of their respective owners. This document is for information only. Specifications are subject to change without notice.

REV 031225

